



# Inspection of Electric Mechanical Equipment



- Electric·mechanical equipment have complex shape!
- Use thermography for easy inspection !


Avio Solution / Short distance-Wide angle measurement

Detachable camera head of Thermo Flex F50 enables "Look up/down", "Inserted into" angle free measurement.

#### (Features)

Realization of angle-free by detachable camera head with environmental resistance. Wide area measurement by focus free wide angle lens (35°/70°) works well in limited space.

Intuitive and simple operation by touch panel, even easy for beginners.






Look down from top



Look up from bottom



Inspection at limited space



Real-time mixing display of visible & thermal imaging \*Image taken by F50B model with 70° field of view

## Thermo Flex F50 detachable camera head Experience of "Ultimate Angle-Free"

## Camera head detachable thermography FREE STYLE Thermo Flex F501



**Specifications** 

opecifications 1 /							
-	Items	F50A-BAS	F50B-BAS	F50A-STD	F50B-STD	F50A-ONL	F50B-ONL
Basic Function	Field of V iew	35°	70°	35°	70°	35°	70°
	Measurement Distance	30cm $\sim$	10cm $\sim$	30cm $\sim$	10cm $\sim$	30cm $\sim$	10cm $\sim$
	Focusing	Not required					
	Pixel Resolution	240×240 Pixels					
	Frame Rate	7.5Hz					
	Temp. Resolution	0.05					
	Measuring Temp. Range	-20~350					
	External Interface	USB2.0 mass storage				USB2.0 mass storage / online	
	IP Rating	IP64					
	Impact Resistance	1m Fall					
	Operating Temp.	-20~70					
	Weight	Approx. 500g (Camera 100g, Controller 400g)					
Main Body Function	Message Recording	V	/	•		<b>✓</b>	
	Voice Recording	V	/	•	/	<b>✓</b>	
	Digital Zoom	<b>✓</b>		/	<b>✓</b>		
	Thermal/Visible Mixing	V	<u>/</u>	\	/	<b>✓</b>	,
	Auto Temp. Setting	V	<u> </u>	<b>\</b>	/	<b>✓</b>	•
	Sky-off	<b>√</b>		/	<b>V</b>		
	Alarm	<u> </u>		<b>✓</b>			
	Point Temp. Measurement	V	<u>/</u>	`	/	<b>✓</b>	
	Auto Tracking Point	V	<u>/</u>	\	/	<b>✓</b>	
	Interval Recording		-	,	/	<b>✓</b>	•
	Fire Recording		-		<b>/</b>	V	<b>′</b>
	2-points Temp. Subtraction		-		<b>/</b>	v	/
	BOX Temp. Measurement		-		<u> </u>	V	<u>'</u>
	Line Profile		-	,	<b>V</b>	V	
	Trend Graph		-		<b>V</b>	V	<b>'</b>
	Real-time transfer		-		-	v	/

Please see detail for brochure.

Avio offers most suitable model for all of your measurement needs.



### NIPPON AVIONICS CO.,LTD.

**Overseas Sales Department Industrial Electronic Products Sales Division** 4206, Ikonobe-cho, Yokohama, 224-0053, Japan

TEL +81-45-930-3596 Fax +81-45-930-3597

E-mail: product-irc-e@ml.avio.co.jp

http://www.avio.co.jp/english/



#### **WARNINGS & CAUTIONS**

· Before using this product, please carefully read the provided Operation Manual "WARNINGS" & "CAUTIONS" section to ensure proper operation. Please do not place the product in high temperature, high humidity or high inert gas environments.

Distri	hutar
DISTIL	Dutoi